

LAVALIER MICROPHONE ELM-1000-3.5

Application : Small and light weight, for Lecture/conference hall

Without wireless system facility

Set to high-frequency characteristics that correspond to speech



SPECIFICATIONS

RoHS II

| | |
|---------------------------------------|--|
| Type | Back Electret Condenser |
| Directivity | Omni-Directional |
| Sensitivity | -36 dB \pm 3dB (0dB=1V/Pa 1kHz) |
| Frequency Response | 50~20,000Hz |
| Maximum Input Sound Pressure Level | 115 dB SPL 1kHz at 1% T.H.D |
| S/N Ratio | 68dB min at 1 kHz (1Pa,A weighted network) |
| Impedance | 1.6 k Ω at 1 kHz \pm 30% (RL=2.0k Ω) |
| Current Consumption | < 0.5mA (RL=2.0k Ω 、Vcc=3.0V) |
| Finish | Black Paint |
| Output Plug | 3.5 ϕ - 3 P Small Plug |
| Dimensions | ϕ 7.8 \times 18 mm (Cord= ϕ 2 \times 1.2m) |
| Weight | \div 15g (include microphone and cord) |
| Accessory | Windscreen----1 Tie Clip-----1 |

FREQUENCY RESPONSE

